

SL- 35 shown with optional Wise Guide

CD ...

Made with pride by an American Company in the USA

B38

Diehl's Mid-Sized Rip Saw, an economically priced machine with the speed and performance of large saws, with guaranteed glue line accuracy. All this coupled with Diehl's legendary quality and durability.





Over 85 years of rip saw manufacturing experience has been put to use developing the SL series of straight line rip saws. The SL-35 features a 15 HP arbor motor, vertical arbor adjustment, and a 2 HP variable speed drive that gives the capacity for higher feed speeds. Diehl's proven chain/race, spindle/arbor and pressure roll system make up the foundation for this saw that produces the industry's most accurate glue line cut, guaranteed. The Diehl SL-35 is the rip saw that you can depend on for continuous quality performance.



The front view illustrates access into the electrically interlocked saw pit area, the dual anti-kickback finger, system the pivoting pressure beam side guard and the adjustment handwheel to accommodate correct positioning of the saw blade for varying thicknesses of material.

The machine's back side is shown with the arbor drive housing cover removed to depict the automatic arbor brake.

| Arbor Motor | 15 HP (11.2 Kw), 20 HP (15 Kw) optional | Voltages Available | 208/240/480/575, 3 phase, 60 cycle |
|---|---|---|--|
| Feed Motor | 2 HP (1.5 Kw) | | 380, 3 phase, 50 cycle |
| Feed Speed | variable, 50 - 140 FPM (12 - 42 mpm) | | w/110 control circuit |
| Stock Capacities | | Spindle Brake | automatic |
| Minimum Thickness | 1/8" (3 mm) | Vacuum | 1 - 6" (152 mm) and 1 - 3" (76 mm) opening 1250 CFM (35c mm) required |
| Maximum Thickness w/14" (355 mm) blade w/16" (406 mm) blade | 1.5" (38 mm) 2.55" (64 mm) | Upper Anti-Kickback Fingers w/Cam Controlled Height Lower Anti-Kickback Fingers in Table | |
| Minimum Length | 12" (305 mm) | Dimensions | 65" (1651 mm) L x 53" (1346 mm) W x 56" (1423 mm) H |
| Saw Blade Arbor Bore | 2" (50.8 mm) | | |
| Throat Capacity | 19" (482 mm) | Weight | net 2,750 lbs. (1250 kg) crated 2,960 lbs. (1345 kg) |
| Arbor RPM Belt Driven | 3450 | | crated for export shipment 3,275 lbs. (1485 kg) |
| Accurate Glue Line Cut (either straight or hollow) | up to 5' (1.5 m) | Worktable Height | nominal 34" (864 mm) |



DIEHL MACHINES

P. O. Box 465, Wabash, IN 46992 • 260-563-2102 • US FAX For Parts And Service 1-800-228-9115 International FAX 260-563-0206 • www.diehlmachines.com